

Rack size 400x400mm & 17x14inch - up to 48 racks / hour



- **Fine filter GENIUS-X²**: up to 40% more removal of food soil
- **315mm usable chamber height** - suitable for glasses, coffee cups & plates
- **Integral DRYING ASSIST** - selectable drying program
- **1.9 litre rinse volume** - low operating costs
- **Rinse pump ACCURINSE** guaranteed rinse volume independent of site pressure
- **SMARTRONIC single button operation** with colour coded status & cycle status indication
- **Patented wide angle FAN wash nozzles** distribute wash water evenly around the wash chamber
- **SELF-CLEANING** cycle
- Deep drawn tank, door and rack slides for maximum hygiene
- **High quality** chemical dispensers
- **“Connect & use”** - Includes 150mm adjustable legs, chemical dispensers, fill and drain hoses, power cord (standard machine 3 phase), non-return valve and drain pump.
- Supplied with 1 glass rack, plus stainless steel grid for use with other rack sizes
- **Hygiene Program active** and **hygiene tab intensive** for removal of calcium and other deposits from wash chamber

Technical Data

1. flexible drain hose 2000mm	Pump-out drain standard
2. fresh water connection: pressure hose 2000mm	Connection size: 3/4" BSP
flow pressure	50-600kPA
water temperature	55-65°C
3. power cord	2000mm
4. hose for detergent	2500mm each
5. hose for rinse aid	
cycle times	75 sec. 120 sec.
water consumption	1.9litres
tank capacity	8 litres
tank heating	2.7kW
power supply	415/50/3 (240/50/1)
booster loading	4.1kW (2.8kW)
total loading	4.8kW (3.4kW)
pump capacity	0.6kW
noise emission	62dB(A)
loading height	315mm

Water hardness should not exceed 3°dH, if higher we recommend using a water softener.

If mineral content is high a demineraliser may be advisable.

